

2 1/2" D

CONCRETE SAND FILL

CLAY SEAL

15"

3 IN. LAYERS

24"

CONCRETE SAND PLUG

CLAY SEAL

15"

3 IN. LAYERS

12"

RUBBER BUSHING 1/2" I.D. X 1" O.D.

PIEZOMETER TIP

12"

DETAIL "A"






Diagram illustrating the components and dimensions of a Fill Control Stake:

- Stake length: 3'-0"
- Board dimensions: 2'-0" x 3'-11" THICK.
- Board material: BLACK WEATHERPROOF MARKINGS ON WHITE WEATHERPROOF FACE.
- Marking spacing: 10 AT 0.7'-1'-0"
- Wood post: 2'-x4" x 8" LONG
- Attachment: EMBANKMENT OR ORIGINAL GROUND.


[illegible][illegible]

SYMBOLS
USED ON PLAN SHEETS

THE ROMAN NUMERALS INDICATE THE NUMBER OF PIEZOMETERS IN THIS GROUP. THE ARABIC NUMERALS AND LETTERS ARE USED IN REFERRING TO TABLE "LOCATION OF PIEZOMETERS" AT FAR LEFT.

	PIEZOMETERS
	SETTLEMENT PLATFORM
	FILL CONTROL STAKES

PIEZOMETERS, SETTLEMENT PLATFORM FILL CONTROL STAKES



MANUAL REVISIONS TO THIS DOCUMENT ARE PROHIBITED.
ALL REVISIONS MUST BE PERFORMED ON
Cadd File: QSA2:200.2001202A.DG

R. N. BAROUTJIAN
T. McMAHON
J.B. JENSEN
D.L. COFFEY

12/20/88
12/20/88
5/1/89
9/25/89
9/10/90